Optional Exhaust Collar 14"x16" AB'' 1x Optional Supply Collar 10"x16" AB'' MOUNTING BRACKET (TYP, OF 4)

MODEL INFORMATION TYPE DIMENSIONS CFM SPECS WEIGHT LENGTH WIDTH HEIGHT EXHAUST PLENUM SUPPLY PLENUM 254 lbs 96" 48" 24" 2417 @ 0.5 ESP 1933 @ 0.12 ESP 254 lbs

OBS.: Installing contractor have the responsability to ensure hood cleareance from limitedcombustible and combustible materials is compliant with local code requirements.

STANDARD COMPONENTS											
MOUNTING BRACKET 12-GAUGE GALVANIZED	Grease Drain	Grease Cup Stainless Steel NSF	Grease Filter Stainless Steel UL 1046								
QTY	QTY	QTY	QTY Length He		Height						
4	1	1	0	16"	20"						
			1	20"	20"						
			3	25"	20"						

SUGGESTED COMPONENTS										
	Supply Collar (Built-in Fire Damper)		Standoff	Incandescent Light . Fixture	Shipping Crate					
Exhaust Collar					Dimensions (in) and Weight (lb)					
16-Gauge Cold Rolled Build		16-Gauge Cold Rolled Build		□ NONE	UL Listed (Included Component)	Length:	100"			
						Width:	52"			
QTY	Size	QTY	Size	5	QTY	Height:	32"			
1	14" x 16"	1	10" x 16"		2	Weight:	334 lbs			

BSSM48-8

STAINLESS STEEL EXHAUST HOOD N.S.F. LISTED. CONFORMS TO NFPA96

Hood Constructed with continuous liquid-tight weld in conformance to IMC 2012 507.7.1.

Hood material: 18 Gauge 430 STAINLESS STEEL (#3 polish) where exposed.





